PCT/IL 2005 / 000367

22 AUG 2005

PA 1347825

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

July 25, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: ***60/558,105***
FILING DATE: ***April 01, 2004***

By Authority of the
Under Secretary of Commerce for Intellectual Property
and Director of the United States Patent and Trademark Office

P. R. GRANT
Certifying Officer

Please type a plus sign (+) inside this box →

PTO/SB/16 (8-00)
Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

13281 U.S.PTO

19249 U.S.PTO 60/558105

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

INVENTOR(S)		
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
Assaf	SHAPPIR	Modein, ISRAEL
Ilan	BLOOM	Haifa, ISRAEL
Boaz	EITAN	Ra'anana, ISRAEL

☐ *Additional inventors are being named on the ^ separately numbered sheets attached hereto*

TITLE OF THE INVENTION (280 characters max)

CONSTANT ERASE CURRENT

Direct all correspondence to: **CORRESPONDENCE ADDRESS**

☒ Customer Number 27130 → *Place Customer Number Bar Code Label here*

OR *Type Customer Number here*

☒ Firm or Individual Name: Eitan, Pearl, Latzer & Cohen Zedek, LLP.

Address	10 Rockefeller Plaza				
Address	Suite 1001				
City	New York	State	New York	ZIP	10020
Country	USA	Telephone	212-632-3480	Fax	212-632-3489

ENCLOSED APPLICATION PARTS *(check all that apply)*

☒ Specification *Number of Pages* 8 ☐ CD(s), Number

☒ Drawing(s) *Number of Sheets* 1

☐ Application Data Sheet. See 37 CFR 1.76 ☒ Other (specify) postcard

METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT *(check one)*

☐ Applicant claims small entity status. See 37 CFR 1.27.

☐ A check or money order is enclosed to cover the filing fees

☒ The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 05-0649

☐ Payment by credit card. Form PTO-2038 is attached.

FILING FEE AMOUNT ($): 160.00

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are:

Respectfully submitted,

Date 01 / Apr / 2004

SIGNATURE

TYPED or PRINTED NAME Guy Yonay

TELEPHONE 212-632-3480

REGISTRATION NO. *(if appropriate)* 52,388

Docket Number: P-6715-USP

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

SAIFUN

Constant Erase Current Patent

Inventors: Assaf Shappir

Ilan Bloom

Boaz Eitan

BEST AVAILABLE COPY

11 March 2004

SAIFUN



Constant Erase Current Patent

- The problem
  - The current invoked during NROM cell erasure with constant voltages is characterized by a high peak which quickly subsides. This peak limits the amount of cell which can be erased simultaneously, due to current consumption limits imposed on the memory product.
  - Furthermore, the efficiency of the constant voltage erase pulse also subsides with time. Hence, during the second half of the pulse a current flows from the cell, yet erasure is very weak.
  - The final outcome is a large current consumption during cell erasure, together with an inherent inefficiency of the constant voltage erase pulse.
  - These two drawbacks translate into a reduced erase rate in the NROM memory product both the number of cells which can be erased simultaneously is limited and the duration of the erase pulse must be long enough to compensate for its inefficiency.

SAIFUN



Constant Erase Current Patent

- Solutions to the problem have included:
  - Erasure of smaller cell populations hence the total peak current does not pass the product spec. limitation. The downside of this method is a slower erase rate, as many sub groups must be erased separately, instead of simultaneous erasure of the entire population.
  - Erasure with lower voltages the applied voltages determine the erase current, hence by the reduction the current subsides. The resultant penalty is the reduction of the erase speed (lower voltages → longer erase pulses).
  - Hole injection into the NROM ONO stack mainly above the n^+ junctions to quickly reduce the erase current the erase current is generated at the n^+ junctions of the NROM cell. Reducing the amount of trapped electrons above this region, by hole injection, reduces this current. The downside is that a two step algorithm must be performed: current reduction, followed by efficient erasure (reduction of cell threshold voltage). One way of achieving this is by two sided NROM cell erasure followed by a single sided NROM cell erasure. The final outcome is a slower erase speed, due to the necessity of two stages.

SAIFUN

Typical Result square pulse with constant voltages







- Two current measurement during 3ms long erase pulses are shown (left) together with the resultant shift of the erased population (32K bits - right).
- The higher the erase pulse voltages (6V vs. 5.2V in the figures) the higher the erase current and the larger the threshold voltage shift (erasure).
- In both case the erase current subsides by ~8× during the pulse.

Erase current vs. Threshold voltage shift



- The above graph shows the reduction of the erase current together with the reduction of the highest threshold voltage in the array population as a function of time during the 3ms erase pulse.
- It can be seen the both the current and the rate of threshold voltage downward shift subside. I.e., erasure becomes inefficient during the course of the erase pulse current continues flowing (~0.4mA in this example), yet the threshold voltage downward shift is very slow.

SAIFUN

Constant Erase Current - Description



- Applied erase voltages, will be ramped from a low value to the desired voltage level the ramping can be limited to a subgroup of the erase voltages, for example: the array gates are fully biased to the desired level/s, the array well is grounded, the array source lines are floated after grounding and the array drain lines are ramped to the desired level.
- The array current consumption will be continuously monitored and the voltage ramp rate adjusted, by a feedback loop, in order to prevent the current from exceeding a pre-specified limit. Efficient current consumption will be achieved regardless of the data content and the bit count.
- Alternatively, the ramp rate can be set to a predefined level without monitoring the array current consumption the strong peak in the erase current can be thus prevented, but the current level will not be constant (see next slide).
- Ramp may be analog (continuous) or digital (stepping).

Erase voltage ramping example

Square vs. Trapezoid pulse





- In this example the erase current and the induced threshold voltage reduction of two pulse shapes is compared: square drain pulse vs. trapezoid drain pulse (all other terminals were set to fixed voltages).
- It can be seen that while erasure is comparable (right figure) the erase current peak was reduced by ~5×. The erase current is not constant in this case, due to the lack of a current monitoring based voltage feedback loop.



Example

Gate stepping erase algorithm with current sensing

- The array gates will be set to the desired negative level and the drain voltage ramped (alternatively the array gates may be ramped, both drain and gate, etc.).
- The erase pulse is completed when either the designated period is reached (t_e) **or** the designated drain voltage is reached and maintained a short period of time (X μs). Hence the actual pulse duration will be $\leq t_e$.
- Following the erase verify operation, the gate voltage will be incremented.
- An extra pulse is applied after the erase verify level is reached.

SAIFUN

Algorithm Flow



Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/IL05/000367

International filing date: 03 April 2005 (03.04.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/558,105
Filing date: 01 April 2004 (01.04.2004)

Date of receipt at the International Bureau: 30 August 2005 (30.08.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)

World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse